

NOTES:


* In Development

** Planned future Product

*** Special

REVISIONS				
ECO	REV	DESCRIPTION	DATE	APPROVED
E0659	X3A	USER DATA AND FREQUENCY OPTIONS	11/8/06	
E0766	X4	ADD CG FREQ BAND , 3.1-3.4 GHZ	05/14/07TG	
E1417	X4A	REMOVE SECURITY OPTIONS 2 & 3 ADD 1 AES	04/10/10	
E1478	X5	ADD HIGH G CRYSTAL OPTION	08/11/10	

MDT-A



RESERVED FOR FUTURE USE.

XX

FREQUENCY

- *P5 - 360 - 400 MHz
- ***P6 - 500 - 700 MHz
- ***F1 - 902 - 928 MHz ISM Band
- L8 - 1435 - 1535 MHz
- L2 - 1700 - 1850 MHz
- ***S5 - 1900 - 2150 MHz
- S2 - 1990 - 2500 MHz
- ***S1 - 2200 - 2400 MHz
- ***F2 - 2400 MHz ISM Band
- S3 - 2400 - 2700 MHz
- CG - 3100 - 3400MHz
- CB - 4450 - 5000 MHz
- ***C9 - 4940 - 4990 MHz
- **CA - 5000 - 5500 MHz
- F4 - 5500 - 5900 MHz
- ***F3 - 5725 - 5875 MHz ISM Band
- ***X7 - 6425 - 6525 MHz
- ***X8 - 6875 - 7125 MHz
- ***X3 - 6800 - 7200 MHz

RF POWER

- A - 100mW
 - B - 200mW
 - C - 1 mW
- (Higher power PA's sold separately!)

SECURITY

- 0 - NONE
- 1 - AES

FW LOAD

- N - Normal Mode
- 4 - 4K
- U - User Data
- 5 - 4K Plus User Data
- A - AUX Data
- 6 - 4K Plus AUX Data

HW OPTIONS

- BLANK - NONE
- H - HIGH G CRYSTAL

Related Products

(Sold Separately)

- # Control Software Application
- # Special Enclosures
 - Anton Bauer Camera Mount
 - Universal Enclosure

ENG/TECH	COBHAM GMS Products		DWG TITLE	
DRAWN RJE			MNI, MDT-A	
ENG	SIZE	DATE	DWG NO	REV
PROD	A	05/14/07	100-MNI0042X5	X5
QC	SCALE:	NONE	SHEET	1 OF 1